



Safety Data Sheet

Brake Fluid DOT 3

Date Issued: 11/18/2013

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: QMI Premium Drum & Disc Brake Fluid DOT3
GENERAL USE: Automotive Aftermarket
PRODUCT DESCRIPTION: Brake Fluid
PRODUCT CODE: 5130

DISTRIBUTOR

ITW Professional Automotive Products
3606 Craftsman Blvd.
Lakeland, FL 33803
Customer Service: 863-665-3338

24 HR EMERGENCY TELEPHONE NUMBERS

Poison Control Center: (877) 800-5533
CHEMTEL: (813) 248-0585

2. HAZARD IDENTIFICATION

GHS CLASSIFICATION

ASPIRATION HAZARD Category 1
EYE IRRITANT – Category 2A

GHS LABEL ELEMENTS



Signal Word: DANGER

Hazard statement: May be fatal if swallowed and enters airways. Causes serious eye irritation.

Precautionary statements: Wash hands thoroughly after handling. Wear eye protection/face protection.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Store locked up. All disposal practices must be in accordance with local, national and international regulations. KEEP OUT OF REACH OF CHILDREN.



Safety Data Sheet

Brake Fluid DOT 3

Date Issued: 11/18/2013

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Concentration, %	CAS
Triethylene glycol monobutyl ether	15-30	143-22-6
Diethylene glycol	15-25	111-46-6
Diethylene glycol monobutyl ether	10-20	112-34-5
Ethanol, 2-(2-propoxyethoxy)-	5-10	6881-94-3

4. FIRST AID MEASURES

EYES: Flush eyes gently with water for at least 15 minutes while holding eyelids apart. Seek immediate medical attention if irritation persists.

SKIN: Remove contaminated clothing. Flush exposed area with large amounts of water.

INGESTION: Seek medical attention. Do not induce vomiting.

INHALATION: Move individual away from exposure and into fresh air. If symptoms do not abate or breathing difficulty develops, seek medical attention. Do not leave individual unattended.

5. FIRE FIGHTING MEASURES

FLASH POINT: 203°F (95°C)

EXTINGUISHING MEDIA: CO₂, dry chemical, or water fog. Use water to cool fire-exposed containers.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Dioxide, Carbon Monoxide.

6. ACCIDENTAL RELEASE MEASURES

Use suitable PPE and ensure adequate ventilation. Prevent runoff into drains, sewers, streams, or other bodies of water. Absorb liquid with vermiculite, floor absorbent or other absorbent material. Scoop or scrape up absorbent and put in the appropriate container for disposal. Flush area with water spray.

7. HANDLING AND STORAGE

HANDLING: Avoid prolonged skin contact, breathing vapors, and contaminated clothing. Use with adequate ventilation. Wear recommended protective equipment. Practice good personal hygiene after handling. Empty containers retain material residue. Do not cut, weld, braze, solder or expose containers to other ignition sources. Follow all MSDS/label precautions even after container is emptied because it may retain product residues.

STORAGE: Keep container tightly closed in a cool, well-ventilated area. KEEP OUT OF REACH OF CHILDREN.



Safety Data Sheet

Brake Fluid DOT 3

Date Issued: 11/18/2013

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits	Concentration	OSHA PEL	ACGIH TLV-TWA
Chemical Name	percent	ppm	ppm
Triethylene glycol monoethyl ether	15-30	NE	NE
Diethylene glycol	15-25	NE	NE
Diethylene glycol monobutyl ether	10-20	NE	NE
Ethanol, 2-(2-propoxyethoxy)-	5-10	NE	NE

ENGINEERING CONTROLS: Use with adequate ventilation.

PERSONAL PROTECTIVE EQUIPMENT

EYES: Appropriate eye protection.

SKIN: Nitrile or other chemical-resistant gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid
Odor and appearance: Clear, light amber
Specific Gravity: 1.041 – 1.065
pH: 7.0 – 11.5
Flash Point, PMCC 203°F (95°C)

10. STABILITY AND REACTIVITY

Stability: Normally stable at ambient temperature and pressure.
Conditions to Avoid: Heat, flame, sparks at temperatures at or above the flash point
Polymerization: Will not occur.
Thermal Decomposition: Carbon monoxide, carbon dioxide

11. TOXICOLOGICAL INFORMATION

Numerical measures of toxicity • - Product

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 1667 mg/kg; Acute toxicity estimate

LD50 Dermal 4606 mg/kg; Acute toxicity estimate

POTENTIAL HEALTH EFFECTS

EYES: Can cause eye irritation.

SKIN: Short contact may cause slight irritation. May absorb through skin upon prolonged exposure.

INGESTION: Harmful or fatal if swallowed. Can result in central nervous system depression. Due to the low viscosity of this material, this material can enter the lungs directly by aspiration during



Safety Data Sheet

Brake Fluid DOT 3

Date Issued: 11/18/2013

swallowing or vomiting. If aspirated into the lungs, this material can cause severe lung damage or death.

INHALATION: Vapors and mist may cause mucous membrane irritation.

CHRONIC TOXICITY: Repeated overexposure to vapors may result in central nervous system depression. Skin absorption can induce central nervous system depression.

CARCINOGENICITY: This material has not been identified as a carcinogen by NTP, IARC or OSHA.

ROUTES OF ENTRY: Skin, Eyes, Ingestion, and Inhalation.

12. ECOLOGICAL INFORMATION

No ecological data are available for this product.

13. DISPOSAL CONSIDERATIONS

Consult federal, state, and local regulations regarding disposal.

14. TRANSPORT INFORMATION

DOT Ground	Not Regulated
DOT Air	Not Regulated
IATA	Not Regulated
IMDG	Not Regulated

15. REGULATORY INFORMATION

TSCA:	All components are on the US TSCA Inventory.
RCRA:	Not listed in 40 CFR Part 302.4.
Cal. Prop. 65	This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

SARA 313 Chemicals	CAS	Percent in product
Diethylene glycol monobutyl ether	112-34-5	10-20
Triethylene glycol monoethyl ether	143-22-6	15-30
Ethanol, 2-(2-propoxyethoxy)-	6881-94-3	5-10



Safety Data Sheet

Brake Fluid DOT 3


Date Issued: 11/18/2013

16. OTHER INFORMATION

HMIS Rating

HEALTH:	1	
FLAMMABILITY:	1	
PHYSICAL HAZARD:	0	
PERSONAL PROTECTION:	B	

NFPA Codes



Date of Preparation or Revision: 11/18/2013

DISCLAIMER:

ITW Professional Automotive Products (ITWProAp) believes the information contained in this data sheet is accurate as of the date compiled. However, ITWProAp makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. ITWProAp disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site (www.wynnsusa.com or www.qmiitw.com).