

QMI PREMIUM SYNTHETIC GEAR OIL SAE 75W-90

– Fully synthetic for longer life and more efficient operation

Description

A vehicle's differential is comprised of two primary gears (the ring and pinion) and other secondary gears (spider, axle), plus various bearings and seals. These gears drive each other by "meshing" together. When two teeth mesh, the entire weight, power and torque of the vehicle applies directly to those two teeth. Since this load bearing surface area is very small, the demand on lubrication is extremely high. Gear oils must perform under these extreme pressure situations while maintaining viscosity in all temperature ranges, perform in both high and low speed environments, remove heat, lubricate bearings, resist moisture and protect against corrosion!

QMI's Full Synthetic formula Premium Synthetic Gear Oil SAE 75W-90 meets or exceeds OEM requirements.



Applications

Differentials and manual transmissions using SAE 75W-90 gear oil.

Features & Benefits

| Features | Benefits |
|----------------------------|--|
| Fully synthetic | Meets or exceeds OE requirements |
| Wear reduction | Increased differential life |
| Improved performance | Less friction related power loss |
| Reduced heat | Diminishes differential oil's greatest enemy |
| Smoother operation | Helps mechanisms operate freely |

SAE Gear Oil Viscosity Grade: 75W-90

API Service Classification: GL-5

Packaging

| <u>Part #</u> | <u>Container Size</u> | <u>Package</u> |
|---------------|-----------------------|----------------|
| GG90 | 55 ounces/1.6 liter | 6 per case |
| GG90D | 55 Gallons | Unit |